

■ **Code:** 104030621

■ **Description:** Flexible rubber Defleco  
High Intensity Grade



#### ■ Technical Characteristics

- Dimensions:  
Body (H/L/W) 33,5x 11,5 x 4,5 cm  
Base (H/L/W) 2,5 x 21 x 15 cm
- Weight:  
total 1,5 kg
- Construction materials:  
high elasticity vulcanized rubber product
- External surface treatments:  
anti-aging red painting of the delineator with 6 inserts H.I.

#### Packaging

- Dimension body (50 pcs):  
40x41x h 35 cm
- Weight :  
55kg
- Dimension base (50 pcs):  
43,5x34x h 30 cm
- Weight:  
25 kg
- Dimensions (600 pcs):  
80x120x h 150 cm
- Weight:  
980 kg

#### ■ Product Description

The delineator is made of profiled vulcanized rubber with high elasticity, high resistance to the hurts and crushing of the vehicles.

The used material permits the delineator to return in the vertical position if hurt from a vehicle, without breaking off from the ground.

The delineator has a trapezium shape that is painted with paints that reduces the ageing and increases the weather resistance.

On the delineator are applied 6 reflective inserts high intensity grade in order to obtain a better visibility.

The product is applied to the ground using its particular base in high elasticity black rubber.

The lower side of the base has a particular shape that permits to obtain the maximum adherence to the ground by the application of a special glue or nails.

#### ■ Working Description

The delineator is used to delimit roadways and to define working zones.

#### ■ Miscellaneous

The correct positioning of the delineator is 12 m in straight roads and 5 m in bends; in the town the frequency is the half, except for different positioning for particular situations.

The delineator must be used to show working zones with duration more than 2 days.

