

■ **Code:** 199000005

■ **Description:** Glue with solvent base to stick the defleco on the road



■ **Features:**

SUPER FIX-D is an adhesive consisting of solution bitumen elastomerized with particular macromolecules that make it particularly elastic and dried product. It is used for gluing the defleco on the road.

■ **Appearance:**

- Black color tixotropic paste

■ **Liquid product features:**

Characteristic	Value	Tolerance	U.M.
Specific weight	1.11	± 0,05	Kg/dm ³
Dry leftover	75	± 1	%

■ **Application Mode:**

SUPER FIX-D must be put on with a brush or a trowel and put a suitable amount of product at the base of the defleco then the user has to put the item on the ground, exerting making a small power, so to permit to the product to stick well on the ground.

■ **Installation Instructions:**

- Equipment: Brush or Towel
- Installation instructions: Ready to use
- Type of diluent: /
- Tool cleaning: Dil S1

■ **Preparation of the ground:**

The base of the defleco must be clean from any traces of adhesives used previously, from dirt and substances extraneous. The road pavement must be clean and clear of non-coherent materials such as stones or gravel.

■ **Consumption:**

- From 30 to 50 defleco each tan

■ **Drying and Hardening:**

- Temperature: Min 5 °C - Max 40°C

■ **Drying or hardening at 23 ° C and 50% U.R.**

- Appearance attachment: 45 minutes
- Set times: 12 h

■ **Characteristics of the dried product:**

Characteristic	Value	Tolerance	U.M.
Elongation at break	1600	± 200	%
Cold flexibility	-25	± 5	°C

■ **Packaging indications:**

- Available colors: Black
- Packaging: 5 kg (net weight 4.75 kg)

■ **Storage temperature:**

- Indications for storage: Min 5 ° C - Max 40 ° C
- Stability in original packaging: 24 months

